




# Piston flow switches, reed switch contact, inlet and outlet 3/4" BSPP male, Type: R36

Pressure and size	Flow sensing: Magnetic piston	Mounting: 3/4" male inlet and outlet	Contact: Reed switch, close on flow rise	Electrical rating	Mounting position	Type
PN10 DN20				≤1A ≤70W ≤250V~		R36



**Main applications:** Product developed for electrical or gas instantaneous water heaters. 3/4" BSPP male water inlet and outlet. Mandatory vertical mounting, with water inlet from the bottom. **Built-in over-pressure valve**

**Functional principle:** Magnetic piston mounted in line with the flow and activating a reed switch through the wall. The return of the piston is by made by gravity. No seal or liquid can pass between the piping system and the electrical contact. Suitable for potable water. Must not be used for water containing magnetic particles or high viscosity liquids, which block the movement of the piston.

**Adjustment:** Can be factory set by adjusting the piston diameter and piston weight

**Body material:** PPO compatible with drinking water.

**Piston:** PPO

**Electrical rating:** Max 1A, Max 70W, Max 250V, resistive load. Use on inductive circuits reduces electrical rating. We recommend to protect the reed switch with contact protection device when used in inductive loads

**Electric contact type:** Normally open, closes by flow rise

**Liquids compatibility:** For use with clean water and liquids without magnetic particles and without chemical incompatibility with PPO Nominal pressure at 20°C: 1MPa (PN10)

**Flow detection set point factory setting limits:**

Close by flow rise: 2,4 to 8 L/min

Open by flow decrease: About 0.4 to 0.5L/min lower than close value

**Nominal diameter:** DN20

**Mandatory mounting position:** on vertical pipes, upstream flow

**Water pipe connection:** Water inlet and outlet: 3/4" BSPP male fitting (Needs gasket). Recommended torque: 7N.m

**Liquids temperature range:** 5 to 80°C

**Ambient temperature range:** 5 to 50°C

**Overpressure valve calibration value:** 1.5 MPa +0.5, -0

**Ingress protection:** IP65

**Electrical connection:** 2 x AWG24 wires (0.2mm<sup>2</sup>), PVC insulation, T80°, standard length 300 mm.

**Options (MOQ apply):**

- Wires with connector or terminals,
- Other wire lengths,
- Other calibration values
- Upside water inlet, (by adding an internal stainless steel piston spring)

### Main references (with 300 mm wires)

References	Close on flow rise (L/min)	Open on flow decrease (L/min)
R36B630240150330	2,4±0,3	1,8±0,3
R36B630300150330	3±0,3	2.6±0,3
R36B630350150330	3,5±0,3	2.9±0,3

Other calibration on request

Because of permanent improvement of our products, drawings, descriptions, features used on these data sheets are for guidance only and can be modified without prior advice

